USON5538762.A

Patent Namber:

5,538,762

Date of Patent: [45]

Jul. 23, 1996

4.961.996 10/1990 Carre et al. 428/421

FOREIGN PATENT DOCUMENTS

363924 11/1989 European Par. Off. 367438 5/1990 European Par. Off. . 386784 9/1990 European Pat. Off.

OTHER PUBLICATIONS

Abstract of JP 61-016910, Jan. 1986. World Patents Index Latest, Derwent Publications Ltd., London, GB: AN 86-065417 & JP-A-61 016 910 (Hitachi Cable KK), Jan. 24, 1986 (abstract).

Primary Examiner—Shrive Beck Assistant Examiner-Erma Cameron Attorney, Agent, or Firm-Fish & Richardson

[57]

ABSTRACT

A method of contacting a substrate having a surface containing hydroxyl groups with a non-aqueous solution containing a material having a chrolosilyl group; washing if desired: coating the substrate with a non-aqueous solvent containing a compound having a fluorocarbon group and a chlorosilane group or a solvent containing a compound containing a fluorocarbon group and an alkoxysilane; and baking the substrate if necessary in order to form a fluorocarbon-based polymer coating film chemically bonded to the substrate surface. The hydroxyl groups on the substrate surface and chlorosilyl groups are reacted to form a thin film having a large number of silanol groups (-SiOH) capable of connecting the polymer coating film to the substrate to form a heat-, weather-, and wear-resistant film on various surfaces.

11 Claims, 6 Drawing Sheets